OIL FIRED FURNACES REFRACTORY CHAMBER PLATFORM









FEATURES:

Refractory combustion chamber

Ready for cooling option

Low speed manual blower switch

4 Speed PSC motor

Beckett (AFG or AFII) or Riello burner

OPTIONAL:

Sealed combustion (Direct vent)



TECHNICAL DATA SHEET

MODELS	OLB53R OLB53F	OLB64R	OHB53F	OHB64F	ODH53F
INPUT (BTU/h)	70,000 @ 105,000	119,000	70,000 @ 105,000	119,000 በ 159,600	70,000 ଜ 105,000
OUTPUT (BTU/h)	59,200 @ 88,200	97,000 @ 129,000	59,400 @ 88,200	୨7,000 ଜ 127,000	58,000 @ 85,700
EFFICIENCY	Up to 86.8%	Up to 85.1%	Up to 86.1%	Up to 85.4%	Up to 85.6%
PARTS WARRANTY	5 years	5 years	5 years	5 years	5 years
COMBUSTION CHAMBER WARRANTY	20 years	20 years	20 years	20 years	20 years
BURNER	Beckett and Riello	Beckett and Riello	Beckett and Riello	Beckett and Riello	Beckett and Riello
EVACUATION	Chimney or Direct vent	Chimney or Direct vent	Chimney or Direct vent	Chimney or Direct vent	Chimney or Direct vent
PROFILE / FLUE	Low Boy / Rear or Front	Low Boy / Rear	High Boy / Front	High Boy / Front	Downflow or Horizontal / Front
WIDTH	21 in	25 in	21 in	25 in	21 in
DEPTH	41 in	49 in	21 in	25 in	21 in
HEIGHT	32 in	40 in	48 in	58¼ in	57 in
SUPPLY	19¾ in x 19¾ in	24 in x 23¾ in	19¾ in x 19¾ in	23¾ in x 23¾ in	19¾ in x 19¾ in
RETURN	19¾ in x 17¾ in	24 in x 21¾ in	18½ in x 13¾ in	21 in x 18 in	19¾ in x 19¾ in
FLUE PIPE	5 in	6 in	5 in	6 in	5 in



3400, boulevard Industriel, Sherbrooke, Québec, J1L 1V8, Canada Téléphone: **1.819.346.8493** | Télécopieur: 1.819.822.4227 info@dettson.ca | **www.dettson.ca**





